Evidence of Performance

Air permeability, Watertightness, Resistance to wind load

Test Report No. 15-001426-PR02

(PB-A01-02-en-01)

New Home for World

Projects LLC

PO Box 594 | PC 320 Sultanate of Oman

Barka Oman

Product Tilt and turn window

Designation System designation: New Home 60 Class A

Performance-relevant product details

Material: PVC-U/white

Overall dimensions (W x H)

920 mm x 1,320 mm

Special features

Results

Client

Air permeability according to EN 12207:1999-11



Class 4

Watertightness according to EN 12208:1999-11



Class 4A

Resistance to wind load according to EN 12210:1999-11/AC:2002-08



Class C4 / B4

ift Rosenheim 17.09.2015

Andreas Graf Deputy Head of Testing Department Construction Product Testing

uf Andreas

Peter Marquardt, Dipl.-Ing. (FH) Operating Testing Officer Construction Product Testing



EN 14351-1:2006+A1:2010

ROSENHEIM

Test standard/s: EN 1026:2000-06 EN 1027:2000-06 EN 12211:2000-06 Correspond/s to the national standard/s (e.g. DIN EN)

Representation



Instructions for use

The results obtained can be used by the manufacturer for preparing the Declaration of Performance in accordance with the Construction Products Regulation 305/2011/EU. The provisions of the applicable product standard have to be observed.

Validity

The data and results refer solely to the tested and described specimen. Classification remains valid as long as the product and the above basis remain unchanged. The results can be extrapolated under the manufacturer's own liability subject to observance of the relevant specifications set out by the applicable product standard. This test/evaluation does not allow any statement to be made on any further characteristics regarding performance and quality of the construction presented; in particular the effects of weathering and ageing were not taken into account.

Notes on publication

The **ift**-Guidance Sheet "Advertising with ift test documents" applies. The cover sheet can be used as an abstract.

The report contains a total of 20 pages.



